


BT19NE4L




- ◆ with Baytrail-D/I/M serial Processor;
- ◆ J1900\J1800\N2806\N2900;
- ◆ DDR3 SODIMM 204 Socket ram slot,Max support8G;
- ◆ 4*Intel I211AT Gigabit Ethernet;
- ◆ 1个RJ45 Port RS232 or RS485(optional)
- ◆ Onboard 32/64/128G EMMC chipset (optional) ;
- ◆ Single-input DC power supply, DC12V power supply;
- ◆ Size: 120 x 120 mm;

Specifications

Processor	CPU	Support Baytrail-I/D/M serial Processor (J1900 N2900 J1800 N2806)
	CPU package	BGA
	Chipset	Support Baytrail-I/D/M serial Processor
	BIOS	EFI BIOS
Memory	Technology framework	Singel channel DDR3 1066/1333/1600MHz
	Capacity	Max support 8GB Ram
	socket	DDR3 SODIMM 204 Socket
Video	Graphic controller	Intel HD Graphics
	HDMI	HDMI Resolution maximum 1920x1080
I/O panel	Interface Port	1*HDMI 2*USB 4*LAN 1 * Quick Power On button with indicator 1 * Restart button
Network	Controller	4*Intel I211AT high performance Gigabit Ethernet Port, RJ45 Port
	Cooler	Aluminum alloy heat sink with fan
Input/Output Interface	USB	1*USB2.0 1*USB3.0 Max support +5V/1A
	COM	1*RJ45 port RS232 or RS485(optional)
	PS/2	NO
Extended bus	Mini-PCle	1*Mini-PCle slot ,support PCIe and USB equipment
storage	SATA	1*SATAII connector, Maximum transmission rate 3Gb/s
	EMMC	On board 32/64/128G EMMC
	M-SATA	1*Mini-PCle M-SATA Scket,support SANDISK Protocol,Maximum transmission rate 3Gb/s
Power Supply	Power Type	Single-input DC power supply, DC12V power supply
	Power consumption	20W
Work environment	Working temperature	-20℃ ~ +60℃
	Storage temperature	-40℃ ~ +85℃
	Working humidity	0% ~ 90%(non-condensing)
	Storage humidity	0% ~ 90%(non-condensing)
Size	size	120 *120 mm
	weight	0.5KG

尺寸



order information

Model	Description	CPU
BT19NE4L-J1900	Integrated Baytrail-D/I/M J1900 Quad core 2.0Ghz up to2.4Ghz DDR3 SODIMM 204 Socket ram slot .max support 8G Integrated 32G/64/128G EMMC chipset (capacity for optional)	J1900, E3845 (Quad Core)
BT19NE4L-N2806	Integrated Baytrail-D/I/M N2806 dual core 1.6Ghz up to2.0Ghz, DDR3 SODIMM 204 Socket ram slot .max support 8G Integrated 32G/64/128G EMMC chipset (capacity for optional)	J1800, N2806 (Dual Core)

packing list

1*driver CD
1*SATA
1*SATA-P cales
1*COM cables

Accessories Optional

Product Name	SPECIFICATION	
USB cable	Length 32CM/2*USB to PIN header	Customiz ed cable optional
COM Cable	Length 32CM, Series to PIN header	
VGA Cable	Length 36CM, 2. 54 VGA to Pin header	
LPT cable	Length 30CM, 2. 54 LPT to Pin header	
More accessories detail contact our salesman, like SSD, RAM, AD adapter, WIFI module, Chassis, etc		