

H-BOX-U3




- ◆ Adopt Baytrail-D/I/M series processor;
- ◆ J1900\J1800\N2806\N2900;
- ◆ Onboard 2GB/4GB DDR3L RAM;
- ◆ Onboard 16/32/64G EMMC (Optional)
- ◆ Provide 1*VGA, 1*HDMI;
- ◆ Support Power on rebooting , control by Jumps ;
- ◆ Single DC input 12V power supply;
- ◆ Size 197*197*33mm;

SPECIFICATION

Model	H-BOX-U3
Size	197*197*33mm
Processor	Support Baytrail-I/D/M series processor (J1900 N2900 J1800 N2806)
Chipset	Support Baytrail-I/D/M series processor
Memory	Onboard 2GB/4GB DDR3 RAM
Expansion Socket	1 DDR3 SODIMM 204 Socket Max.up to 8G
Network	Onboard 1*1000M LAN RJ45 ports
Audio	Onboard HDA ALC662
Storage	1*MINISATA support SSD and 1*SATA2(Optional) ; 1*SATA1 and 1*SATA_HDD(Optional), 1*16/32/64G EMMC (Optional)
Colour	Silver
Front I/O ports	1*LAN 1*HDMI 1*VGA 1*DC 1*MIC-IN 1*LINE-OUT 1*USB3.0 1*USB2.0 2*WIFI antenna interface
Rear I/O ports	1*Power Switch 2*USB2.0
Standard Components	1*12V 60W power adapter 2*WIFI antenna

H-BOX-U3**Size**

Unit: mm

**ORDER INFORMATION**

Model	SPECIFICATION	CPU(Optional)
H-BOX-U3	Intel Baytrail Series (J1900/N2806/N2900/J1800) Onboard 2GB/4GB DDR3L memory Onboard 16/32/64G EMMC (Optional)	J1900/N2806/N2900/J1800

Packing List

1*Power Adapter
1*CD driver

Accessories(Optional)

Model	SPECIFICATION	
Internal USB Cable	Cable length 32CM, 2*USB To Pin Header	Customized cable optional
Internal COM Cable	Cable length 32CM, COM (DB9) to Pin Header	
Internal VGA Cable	Cable length 36CM, VGA to Pin Header	
Internal LPT Cable	Cable length 36CM, LPT to Pin Header	
More accessories, please contact Salesman (SSD, DC power supply, 3G/4G/WIFI model, LCD display etc)		

