

# PPC-HU12A



## Main features

- ◆ Integrated Intel 5<sup>th</sup> Mobile Broadwell-U single chipset CPU;
- ◆ 12inch TFT LED display and 4 wires resistive Touch panel
- ◆ Front panel protection Rating: IP65
- ◆ Support SATA and M-sata storage
- ◆ Support wireless 3G/WIFI Internet access
- ◆ 2\*RS422/485 is DB9 interface 4 three-wire RS-232 (Phoenix terminal interface),
- ◆ DC12V5A power supply (optional 9-36V wide voltage supply)
- ◆ Sealed and fanless design

## Overview


The PPC-HU12A is a cost-effective 12-inch ultra-thin LCD industrial tablet PC with Broadwell-U processor and a compact fanless embedded system for high performance computing. With High durability design, front panel protection grade IP65, strong aluminum alloy casing, 4-wire resistive touch screen, support 6 serial ports, 2 USB ports and 2 Gigabit Ethernet ports to meet various industrial applications.


## Specifications

Processor	CPU	Intel® Core™5th Broadwell-U Soc i3/i5/i7 processor
	Memory	Integrated 2GB\4GB DDR3 1066/1333/1600MHz,1 slot can be added, up to be 12GB
	storage	Onboard SSD16/32/64/128G (optional) , SATA and MSATA, HDD and SSD (optional)
	Internet (LAN)	2*Intel I211AT Gigabit Lan Port
	I/O Port	2*RS422/485/232 is DB9 Interface 4 three-wire RS-232 (Phoenix terminal interface), 2*USB2.0,2*USB3.0, 1*14BIT GPIO Port, 1*LINE OUT 1*MIC, 2*Wifi antenna Port, 1*power switch button, 1*HDMI Max resolution support 3200*2000@60HZ
	Expansion bus	1*full size Mini-PCIE socket
	Watch -dog timer	0-255 second, Sample code optional
Physical characteristics	size	316.6*253.6*62.5mm
	weight	2.75Kg
OS Support	Operate System	Support Windows 7/Windows8/Windows8.1/Windows10/Linux
Power type support	input Voltage	DC12V5A power supply (optional 9-36V wide voltage supply)
	consumption	35W
LCD display	Display type	12inch TFT LED
	Max resolution	1024*768
	View	80 (left), 80 (right), 70 (UP), 70 (Down)
	Lumens (cd/m <sup>2</sup> )	350cd/m <sup>2</sup>
	Contrast	400:1
	Backlight Life	30,000 hrs (Min.)
TOUCH PANEL	TYPE	4 Wires Resistive touch panel
	Light Transmittance	≥85%
	Controller Interface	USB Port
	Durability(Touch Times)	>3500 million times
ENVIRONMENT	Working Temperature	-20℃ ~ +60℃
	Storage Temperature	-40℃ ~ +85℃
	Relative humidity	0% ~ 90%Relative humidity, none condensation
	EMC	CE, FCC Class B, BSMI
	CERTIFICATE	CB, CCC, BSMI, UL
	Front panel protection	Front panel IP65

size

单位：mm



Order information		Panel I/O
Model	description	
PPC-12A	With TPC90D Motherboard (I3-5010U/I5-5200U/I7-5500U)	